



**CANADIAN**



# HAND PORTABLE FIRE EXTINGUISHERS SPECIFICATION AND SUBMITTAL SHEET

Quality is Behind the Diamond®

CUSTOMER NAME: \_\_\_\_\_

ITEM: \_\_\_\_\_

MODEL NUMBER(S): \_\_\_\_\_

ARCHITECT: \_\_\_\_\_

SUBMITTED BY: \_\_\_\_\_

DATE: \_\_\_\_\_

PROJECT: \_\_\_\_\_

QUANTITY: \_\_\_\_\_

APPROVED BY: \_\_\_\_\_

**FEATURES:**  
**ALL METAL VALVES**

**EASY AND LESS COSTLY  
MAINTENANCE AND RECHARGE**

**BAR CODE LABELS**

**U.S. COAST GUARD APPROVED  
WITH DESIGNATED BRACKET**

**OPERATIONAL TEMPERATURE  
RANGE -65°F TO +120°F**

## DRY CHEMICAL FIRE EXTINGUISHERS

ALUMINUM VALVE

BRASS VALVE



A620T

B417TX  
403TX-DS  
410T

B500X  
B500TX  
B402X  
B402TX  
B479T

B459X

B456X

A411X

B424X

B441X  
B447  
460

423X  
408X  
415

692X  
693X

AGENT TYPE										
VALVE TYPE	ANODIZED ALUMINUM					CHROME PLATED BRASS				
DESIGN	NOZZLE	HOSE & NOZZLE				HOSE & NOZZLE				
MODEL NUMBER	B417TX	B500X/B500TX	B402X/B402TX	B456X	A411X	B424X	B441X	423X	692X	
ULC RATING	1A:10B:C	3A:10B:C	3A:40B:C	6A:80B:C	10A:120B:C	2A:10B:C	6A:80B:C	10A:120B:C	10A:120B:C	
CAPACITY (LBS.)	2.5	5	5	10	20	5	10	20	30	
SHIPPING WT. (LBS.)	5.25/5.5	9.25/9.5	9.25/9.5	18	38	10.5	19	39	54	
HEIGHT (IN.)	15.5	15.25	15.25	20	24	15.5	20.5	24	26.125	
WIDTH (IN.)	5.75	7.25	7.25	7.75	10.25	8	8.75	10.25	11	
DEPTH (IN.)	3	4.25	4.25	5	7	4.25	5	7	8	
RANGE (INITIAL- FT)	9-15	12-18	12-18	15-21	15-21	12-18	15-21	15-21	15-21	
DISCHARGE TIME (SEC.)	10	14	14	20	30	14	20	30	34	
FM APPROVED	YES	YES		YES	YES			YES		
OPTIONAL CHROME CYLINDER	YES	YES	YES	YES		YES	YES			
INCLUDED BRACKET	VEHICLE	WALL/VEHICLE			WALL	WALL				

AGENT TYPE	REGULAR DRY CHEMICAL				
VALVE TYPE	ANODIZED ALUMINUM			CHROME PLATED BRASS	
DESIGN	NOZZLE		HOSE & NOZZLE		
MODEL NUMBER	A620T	B403TX-DS	B459X	B447X	408X
ULC RATING	2B:C	10B:C	40B:C	60B:C	120B:C
CAPACITY (LBS.)	1	2.5	6	10	20
SHIPPING WT. (LBS.)	2.5	5.5	9	19	39
HEIGHT (IN.)	10	15.5	16.187	20.25	24
WIDTH (IN.)	3.5	5.75	8.5	8.75	10.25
DEPTH (IN.)	2.63	3	5	5	7
RANGE (INITIAL- FT)	5-8	9-15	12-18	15-21	15-21
DISCHARGE TIME (SEC.)	10	10	13.6	18	28
FM APPROVED		YES		YES	YES
OPTIONAL CHROME CYLINDER	YES	YES		YES	
INCLUDED BRACKET	VEHICLE			WALL	

AGENT TYPE	PURPLE K DRY CHEMICAL				
VALVE TYPE	ANODIZED ALUMINUM		CHROME PLATED BRASS		
DESIGN	NOZZLE		HOSE & NOZZLE		
MODEL NUMBER	B410T	B479T	B460	415	693X
ULC RATING	10B:C	30B:C	80B:C	120B:C	120B:C
CAPACITY (LBS.)	2.5	5	10	20	30
SHIPPING WT. (LBS.)	5.5	9.5	19	39	54
HEIGHT (IN.)	15.5	15.25	20.5	24	26.125
WIDTH (IN.)	5.75	7.25	8.75	10.25	11
DEPTH (IN.)	3	4.25	5	7	8
RANGE (INITIAL- FT)	9-15	12-18	15-21	15-21	15-21
DISCHARGE TIME (SEC.)	10	12	22	28	33
FM APPROVED	YES		YES	YES	
OPTIONAL CHROME CYLINDER	YES	YES	YES		
INCLUDED BRACKET	VEHICLE			WALL	

**WATER, AFFF & FFFP FOAM, WATER MIST, WET CHEMICAL, CARBON DIOXIDE, HALOTRON I and CLASS D FIRE EXTINGUISHERS**



240X 250X B272XN B260X 332X 322X 330X 331X 384T B385TSX 397X B386TX 398X B570X B571

AGENT TYPE	WATER	WATER MIST	ATC FOAM	WET CHEMICAL	CARBON DIOXIDE			
DESIGN	HOSE & NOZZLE	HOSE & NOZZLE	HOSE & AIR ASPIRATED NOZZLE	HOSE & SPRAY NOZZLE	HORN	HOSE & HORN		
MODEL NUMBER	240X	B272XN	250X	B260X	322X	330X	331X	332X
ULC RATING	2A	2A:C	3A:20B	2A:K	5B:C	10B:C	10B:C	10B:C
CAPACITY	2.5 GAL	2.5 GAL	2.5 GAL	6 LITER	5	10	15	20
SHIPPING WT. (LBS. EMPTY)	7.5	8	11	22.5	13.1	28.25	37.75	50.75
HEIGHT (IN.)	24.5	24.5	24.5	19	17.75	24	30	30
WIDTH (IN.)	9	11	9	9	8.25	12	12	13
DEPTH (IN.)	7	7	7	7	5.25	7	7	8
RANGE (INITIAL- FT)	45-55	10-12	10-12	10-12	3-8	3-8	3-8	3-8
FM APPROVED	YES		YES		YES	YES	YES	YES
DISCHARGE TIME (SEC.)	55	80	55	53	9	11	15	19
INCLUDED BRACKET	WALL	NM WALL	WALL	WALL	WALL	WALL	WALL	WALL

AGENT TYPE	HALOTRON™ I					SODIUM CHLORIDE	COPPER
VALVE TYPE	ANODIZED ALUMINUM		CHROMED BRASS			HOSE & HORN OR WAND APPLICATOR	
DESIGN	NOZZLE					HOSE & HORN OR WAND APPLICATOR	
MODEL NUMBER	A384T	B385TSX	B386TX	397X	398X	B570X	B571
ULC RATING	1B:C	2B:C	5B:C	1A:10B:C	2A:10B:C	FM Approved	FM Approved
CAPACITY (LBS.)	1.4	2.5	5	11	15.5	30	30
SHIPPING WT. (LBS.)	3.25	5.25	9.5	22.5	27.5	53	53
HEIGHT (IN.)	10	15.5	15.25	21.88	21.88	35	35
WIDTH (IN.)	3.5	6.38	5.75	9.25	9.25	13	13
DEPTH (IN.)	2.63	3	4.25	6	6	8	8
RANGE (INITIAL- FT)	6-8	6-10	9-15	9-15	12-18	3-6	3-6
DISCHARGE TIME (SEC.)	9	9	9	9	14	24	18
OPTIONAL CHROME CYLINDER	YES	YES	YES				
MINIMUM CONFINED SPACE REQUIREMENTS (CU. FT.)	196	350	700	1540	2170		
FAA APPROVED MODEL				YES	YES	YES	YES
INCLUDED BRACKET	VEHICLE	VEHICLE	VEHICLE	WALL	WALL	WALL	WALL

**BRACKETS:**

AGENT TYPE	SIZE (CAPACITY)	MODEL	CYL. DIA. (INCH)	INCLUDED BRACKET	USCG BRACKET	OPTIONAL BRACKETS	RUBBER STRAP BRACKETS	899 DOLLY OPTION
WATER	2.5 GAL.	240X	7	1007 WALL	N/A	810	864	YES
WATER MIST	2.5 GAL.	B272XN	7	14315 WALL	N/A	810NM	N/A	
WET CHEMICAL	6 LITER	B260X	7	1007 WALL	810	810	N/A	
HALOTRON® I	1.4 LB.	A384T	2.63	845 VEHICLE	N/A	845S	N/A	
	2.5 LB.	B385TSX	3	817S AIRCRAFT	N/A	817S	860	
	5 LB.	B386TX	4.25	818 V/MARINE	818, 821, 861H	818S, 821, 821S, 807	860	
	11 LB.	397X	6	0575 WALL	812	812	N/A	
	15.5 LB.	398X	6	0575 WALL	812	812	N/A	
ABC DRY CHEMICAL	2.5 LB.	B417TX	3	4834 WALL / 817 VM	817	817S	860	
	5 LB.	B402X / B402TX	4.25	16591 WALL / 818 VM	818, 821, 861H	818S, 821, 821S, 807	860	
	5 LB.	B500X / B500TX	4.25	16591 WALL / 818 VM	818, 821, 861H	818S, 821, 821S, 807	860	
	5 LB.	B424X	4.25	16591 WALL	821, 861H	821, 821S, 807	860	
	10 LB.	B456X	5	0546 WALL	808, 809, 895	808, 809, 846, 889, 889HB, 895	862	
	10 LB.	B441X	5	1007 WALL	809, 895	808, 809, 889HB, 895, 846	862	
	20 LB.	A411X	7	0577 WALL	810	810	864	YES
REGULAR DRY CHEMICAL	20 LB.	423X	7	0577 WALL	810	810	864	YES
	30 LB.	692X	8	0577 WALL	811	811G	864	YES
	1 LB.	A620T	2.63	845 VEHICLE	N/A	845S	N/A	
	2.5 LB.	B403TX-DS	3	4834 WALL / 817 VM	817	817S	860	
PURPLE K DRY CHEMICAL	6 LB.	459X	5	1007 WALL	809	809	862	
	10 LB.	B447	5	1007 WALL	809, 895	808, 809, 846, 889HB, 895	862	
	20 LB.	408X	7	0577 WALL	810	810	864	YES
	2.5 LB.	B410T	3	817 V/MARINE	817	817S	860	
CARBON DIOXIDE	5 LB.	B479 / B479T	4.25	16591 WALL / 818 VM	818, 821, 861H	807, 818S, 821, 821S, 861H	860	
	10 LB.	B460	5	1007 WALL	809, 895	808, 809, 846, 889HB, 895	862	
	20 LB.	415	7	0577 WALL	810	810	864	YES
	30 LB.	693X	8	0577 WALL	811	811G	864	YES
	5 LB.	322X	5.25	0546 WALL	809	809	862	
CARBON DIOXIDE	10 LB.	330X	7	0575 WALL	810	810	N/A	
	15 LB.	331X	7	0575 WALL	810	810	864	YES
	20 LB.	332X	8	0575 WALL	811	811	864	YES